

F-1300B / F-1300W

The speaker shall be a two-way bass reflex enclosure suitable for ceiling or wall mounting. The low frequency component shall be a 5" (13 cm) cone-type woofer. The high frequency component shall be a 1" (25 mm) dome tweeter.

The speaker shall be rated at 8 ohms. The output sound pressure level at a distance of 1m with a 1W input level applied shall be 90 dB SPL. The rated power handling shall be 50 W continuous pink noise and 150 W continuous program. The speaker shall have a frequency response of 80 - 20 kHz. The rated nominal coverage angles shall be 110 degrees horizontal and 100 degrees vertical.

The speaker enclosure shall be constructed of high-impact polystyrene resin. The speaker shall be available in white or black. The grille shall be a surface-treated, perforated steel plate with painted finish. The joint bracket and wall bracket shall be stainless steel with painted finish. The speaker bracket shall be die-cast aluminum with painted finish. The input connector shall be a spring-clip push terminal.

The unit shall be compact and lightweight with dimensions of 6.38" x 9.84" x 6.34" (162 x 250 x 161 mm) and a weight of 6.83 lbs (3.1 kg).

The speaker shall be a TOA model F-1300B / F-1300W.
The board hanger bracket shall be the HY-BH10B.
The ceiling mount bracket shall be the HY-CM10B / HY-CM10W.
The cluster bracket shall be the HY-CL10B.
The 8" in-wall subwoofer shall be the HB-1.
The 10" subwoofer shall be the FB-100.

=====

F-1300BT / F-1300WT

The speaker shall be a two-way bass reflex enclosure suitable for ceiling or wall mounting. The low frequency component shall be a 5" (13 cm) cone-type woofer. The high frequency component shall be a 1" (25 mm) dome tweeter.

The speaker shall include a built-in 70.7/100 V matching transformer. The rear panel shall have screwdriver-adjustable tap settings of: 30 W, 15 W, 5 W, 1.5 W and 0.5 W at 70.7 volts. The output sound pressure level at a distance of 1 m with 1 W of input power applied shall be 90 dB SPL. The rated power handling shall be 30 W continuous pink noise. The speaker shall have a frequency response from 80 to 20k Hz. The rated nominal coverage angles shall be 110 degrees horizontal and 100 degrees vertical.

The speaker enclosure shall be constructed of high-impact polystyrene resin. The speaker shall be available in white or black. The grille shall be a surface-treated, perforated steel plate with painted finish. The joint bracket and wall bracket shall be stainless steel with painted finish. The speaker bracket shall be die-cast aluminum with painted finish. The input connector shall be a spring-clip push terminal.

The unit shall be compact and lightweight with dimensions of 6.38" x 9.84" x 6.34" (162 x 250 x 161 mm) and a weight of 6.83 lbs (3.1 kg).

The speaker shall be a TOA model F-1300BT / F-1300WT.
The board hanger bracket shall be the HY-BH10B.
The ceiling mount bracket shall be the HY-CM10B / HY-CM10W.
The cluster bracket shall be the HY-CL10B.
The 8" in-wall subwoofer shall be the HB-1.
The 10" subwoofer shall be the FB-100.

=====

F-1300BTWP / F-1300WTWP

The indoor/outdoor speaker shall be a two-way bass reflex enclosure suitable for indoor and outdoor installation. The low frequency component shall be a 5" (13 cm) cone-type woofer. The high frequency component shall be a 1" (25 mm) dome tweeter.

The speaker shall include a built-in 70.7/100 V line matching transformer. The rear panel shall have screwdriver-adjustable tap settings of: 30 W, 15 W, 5 W, 1.5 W and 0.5 W at 70.7 volts. The output sound pressure level at a distance of 1 m with 1 W of input power applied shall be 90 dB SPL. The rated power handling shall be 30 W continuous pink noise. The speaker shall have a frequency response from 80 to 20k Hz. The rated nominal coverage angles shall be 110 degrees horizontal and 100 degrees vertical.

The speaker enclosure shall be constructed of high-impact polystyrene resin. The speaker shall have an IEC 529 splash-proof rating of IP-X4 and an operating temperature range of 14° F to 122° F (-10° C to +50° C). The speaker shall be available in white or black. The grille shall be a surface-treated, perforated steel plate with anticorrosive paint. The joint bracket and wall bracket shall be SUS304 stainless steel. The speaker bracket shall be die-cast aluminum with painted finish. The input connector shall be a spring-clip push terminal with removeable splash-proof terminal cover.

The unit shall be compact and lightweight with dimensions of 5.12" x 7.95" x 5.16" (130 x 202 x 131 mm) and a weight of 4.41 lbs (2 kg).

The indoor/outdoor speaker shall be a TOA model F-1300BTWP/ F-1300WTWP.
The indoor/outdoor pole mount bracket shall be the YS-60B.