

Security Surveillance TFT LCD Monitors



15" IK-H550V



17" IK-H750V



19" IK-H950V

General Features

- Loop through Composite Video (2BNC, 17", 19" only)
- S-Video(Y/C), Analog VGA and Audio(2 Speakers)
- 1280 x 1024 Pixels Resolution (17", 19" only)
- 16.2 million colors
- Fast Response Time 25msec.
- NTSC & PAL Compatible
- On-Screen Display Control (OSD)
- Power AC 100V ~ 240V (no adaptor required)
- All Safety Standards (FCC, CE, UL, TCO)
- Space Saving, Ultra Slim Design

Specifications

Description		IK-H550V	IK-H750V	IK-H950V
Panel	Type	Amorphous Active Matrix Super TFT LCD		
	Viewable Size	15"(TN) Diagonal	17"(TN) Diagonal	19"(TN) Diagonal
	Pixel Pitch	0.297mm x 0.297mm	0.264mm x 0.264mm	0.294mm x 0.294mm
	Number of Pixels	1024x768	1280x1024	1280x1024
	Display Colors	16 Million Colors		
	Brightness	250cd/m2	300cd/m2	250cd/m2
	Contrast Ratio	300:1	350:1	500:1
	Response Time	25 msec.		
	Viewing Angle (L/R)	75/75	75/75	85/85
	Viewing Angle (U/D)	75/60	75/60	85/85
Frequency	Horizontal	30 ~ 80KHz		
	Vertical	56 ~ 75Hz		
Microprocessor	Digital Control	Yes		
Multimedia	Sound	1W/ch		
Plug & Play	DDC	Yes (DDC1/2B)		
Display Area	Max. W x H	11.9x11.3 in.	13.3x10.6 in.	14.8x11.9 in.
Key Functions	Front	Source, Menu(Exit), Auto(Select), Power		
		Brightness(-), Contrast(+), Volume		
Power	Embedded DC Adaptor	90/240V (50 ~ 60Hz) input		
Input Signal	Input	Analog RGB, BNC, S-VHS		
	Output	BNC (Loop OUT, 17"19" only)		
Compatibility	Analog RGB	VGA, SVGA, XGA, SXGA		
		Normal & Ergonomic Modes		
Regulations	EMI	FCC		
	Safety	CE, UL		
Wall Mount	Low Radiation	TCO '99		
		VESA Standard		
Weight	Product	8.4 lbs	12.8 lbs	13.6 lbs
	Shipping	11.7 lbs	15.8 lbs	17.2 lbs
Dimensions	Product	14x13.6x5 in.	15x8x16.4 in.	16.5x7.9x17.2 in.
	Shipping	16.5x16x6.8 in.	17.5x7.8x18.7 in.	20.5x8.5x20.9 in.
Power Consumption	Maximum	40 Watts		
	DPMS	Under 3Watts		
		These specifications are subject to change without notice.		