

CA-115/CA-130/ca-160

CA-115

-----  
(35W Max.) Car Amplifier  
-----

Car amplifier, fits in standard car radio compartment, 2 microphone inputs, 1 AUX input, level control for microphones, all controls on the front, including hand-held microphone with integrated talk button.

Frequency response: 100-10,000 Hz (+/-3 dB)  
Total harmonic distortion: < 5% at 1 kHz and 15 W  
Inputs: 2 x Mic: 4 mV / 600 ohm  
1 x AUX: 500 mV / 10 k ohm  
Output: 4 or 8 ohm  
Output power: 15 W  
Voltage: 13,2 V DC (10-16 V)

Manufacturer: TOA  
Model: CA-115

CA-130

-----  
(60W Max.) Car Amplifier  
-----

Car amplifier, fits in standard car radio compartment, 2 microphone inputs, 1 AUX input, level controls for microphones, all controls on the front, including hand-held microphone with integrated talk button.

Frequency response: 100-10,000 Hz (+/-3 dB)  
Total harmonic distortion: < 5% at 1 kHz and 30 W  
Inputs: 2 x Mic: 4 mV / 600 ohm  
1 x AUX: 500 mV / 10 k ohm  
Output: 4 or 8 ohm  
Output power: 30 W  
Voltage: 13,2 V DC (10-16 V)

Manufacturer: TOA  
Model: CA-130

CA-160

-----  
(120W Max.) Car Amplifier  
-----

Car amplifier, fits in standard car radio compartment, 2 microphone inputs, 1 AUX input, level controls for microphones, all controls on the front, including hand-held microphone with integrated talk button

Frequency response: 100-10,000 Hz (+/-3 dB)  
Total harmonic distortion: < 5% at 1 kHz and 30 W  
Inputs: 2 x Mic: 4 mV / 600 ohm  
1 x AUX: 500 mV / 10 k ohm  
Output: 4 or 8 ohm  
Output power: 60 W  
Power supply: 12 V DC

Manufacturer: TOA  
Model: CA-160