

MW-41BT

Audio Interface with USB and Bluetooth

TOA's new generation audio interface has expanded its capabilities. The control panel shall be equipped with Microphone, Aux (3.5mm), USB and Bluetooth inputs, and one Mono balanced output. The microphone will have the highest priority over the other inputs. The panel will include input selection button, volume control, Bluetooth input and USB input that is compatible with MP3 and WAV files. LED light indicators in blue. Construction of the interface is as follows;
Panel: Aluminum, Sandblasting, Silver, with decorative Sheet: Acrylic, Black. Power source will be 100-240V AC 50/60Hz with power consumption of 3W. Dimensions of the panel shall be 120 (W) x 120 (H) x 40.2 (D) mm (4.72" x 4.72" x 1.58") and it shall weigh 0.2 kg (0.44lbs). The panel fits in a standard 2-gang electrical box. The MW-41BT includes an AC power adaptor, remote control, box mounting screws and RJ conversion socket. The audio panel shall have two optional lock boxes for protection. the BX-41F flush mount and the BX-41S surface mount. Lock boxes include 2 keys each. Also, 2 Gang boxes, YC-823, YC-822, YC-302, YC-531HSW

The audio interface shall be TOA model MW-41BT

The flush mount lock box shall be TOA model BX-41F

The surface mount lock box shall be TOA model BX-41S