

TOA Canada's Discontinued and B-Stock Products.

Updated July 29, 2026

Part No.	Material Description	Condition	Qty. Avail.
Condition B1 - Factory sealed discontinued items or factory seal broken but otherwise like new. 30% off your price level.			
A-2060 CU	MIXER AMPLIFIER	B1	1
A-2240 CU	240W mixer/amplifier (5 channel input, Mic./Line/PBX), phantom power, auto-mute	B1	1
AT-100 AM QV	10k ohm volume control	B1	1
AT-10K AM QV	100W Decora-Style 10k ohm single point volume control	B1	1
BS-1030W	COMPACT SPEAKER (WHT)	B1	2
BS-678	6W, 2 x 2.5" speakers, Wall mount , wood cabinet, 70V (sold in pairs)	B1	2
BS-680FC	6W, 6" double cone speaker, Wall mount , metal body, 70V	B1	1
BS-680U	6W, 6" double cone type spkr., surface mount, metal case UL/ULC, 25V/70V	B1	2
CS-304	6W, 2 x 2.5" speakers, surface mount, metal case UL/ULC,	B1	1
D-001T B00	9000 SERIES PLUG-IN MODULE	B1	1
EM-380-AM F00	GOOSENECK MICROPHONE	B1	1
EQ-0101A Q	Equalizer for HA-1010** (special order)	B1	2
EV-350R L	Digital Record/Playback Announcer, mountable memory c	B1	4
H-2 EX	12W, 2-way, dome-shaped 4" speaker, + 1" tweeter, wall/ceiling-mount, 4 ohm/70V	B1	1
HY-1200HW	Mounting bracket, for horizontal speaker mounting, for HS-	B1	2
HY-1200VB	Mounting bracket, for vertical speaker mounting, for HS-1200 speakers, black	B1	1
HY-1200VW	Mounting bracket, for vertical speaker mounting, for HS-12	B1	1
HY-C0801W	Ceiling Mount Bracket for HS series speakers, HS-1200WT, HS-1500WT	B1	1
HY-W0801W	Wall mount bracket for, HS-1200BT, HS-1500BT, white	B1	2
IP-A1SC15 E00	Network Horn speaker, 15 W (at PoE+), 8 W (at PoE), ONVIF compatible	B1	1
IP-SC15MC Q D00	Network Horn speaker, up to 15 W (+/- 10%), ONVIF compa	B1	1
IR-801AF US	Single channel (A), wireless tuner w/ output to control Infrared Mic.	B1	1
IT-450	Input transformer	B1	1
M-21S D00	900 Series Module: Mic. module, remote volume, gain, phantom, screws, 600 ohm	B1	1
M-41S D00	900 Series Module: Mic. module, mute-send, screws, 600	B1	1
M-800RCTB-AM D00	REMOTE AUDIO CONTROL PANEL W/ DISPLAY	B1	1
MW-41BT-AM D00	Audio Interface w/ USB & Bluetooth (power supply incl.)	B1	1
N-SP80MS1 C00	IP Audio Window Intercom Kit, 2-way (power supply incl.), Weather Resistant	B1	1
P-912MK2 UL D00	PA AMPLIFIER	B1	1

PE-604BU	60W Pendant 5" speaker, UL1480 UUMW, ULC-S541, 8 ohm/70V/100V, black	B1	1
S2.4-RX2-G3	2 channel Receiver w/ LCD (1 Unit size), 16 available char	B1	1
SC-615	15W Paging horn, 8 ohm, incl. bracket	B1	1
SP-11N AM D00	900 Series SIP module complete w/ AD-1215P (Asterisk & i	B1	1
SP-201	Speaker horn bracket for wall mount, and on w/ YS-60B	B1	1
SR-WB3	Wall mounting bracket, SR-H3S, SR-H3L, SR-H2S, SR-H2L	B1	1
SR-WB4	Slim type, wall mount bracket, SR-S4L	B1	5
TS-822 Y E00	TS-820 system: Delegate Unit	B1	3
TT-104B 304L	Program timer w/ 4 outputs & controls 4 different broadcasts	B1	1
UC-4SC615 Q E01	Network Horn Speaker with Microphone	B1	1
WM-2100 01	Portable Receiver, 5 channels	B1	2
WM-5265 H01	UHF Wireless Handheld Mic. for Speech/Vocals - 64 chan	B1	1
WT-4820 US	WIRELESS TUNER	B1	1
ZM-9012 B00	9000M2/M-864D Remote Control Panel - 9000M2 use reqs	B1	2

Part No.	Material Description	Condition	Qty. Avail.
Condition B2 - Packaging disturbed or cosmetic damage to product and/or refurbished. 40% off your price level.			
A-2240 CU	MIXER AMPLIFIER	B2	1
A-906MK2 UL D00	60W mixer power amplifier (8 channel input slots, reqs. 900 series modules), permits paging priority	B2	2
BA-260 CU	60W, 1 input mixer/amplifier, one line input, 4 ohm/25V/70V	B2	1
BS-1034S	10W, Slim box speaker, silver, 70V	B2	1
C-001T B00	9000M2 Series Module: I/O control module, 8 inputs 8 outp	B2	1
D-001T	9000M2 Series Module: Dual Mic./line input w/ DSP module & balanced	B2	1
EV-20R US D00	Digital sound repeater, 3W amp, USB interface, line O/P, r	B2	1
F-2352C	30W, co-axial 5", ceiling speaker + dome tweeter, 8 ohm or 25/70V selectable taps, c/w Reinforcement Ring & metal back can	B2	1
H-3 EX	30W, wide dispersion, 2 x 4" speaker, + 1" tweeter, wall mc	B2	3
HX-7W-WP F00	SPEAKER SYSTEM	B2	1
HY-C0801	Ceiling Mount Bracket for HS series speakers, HS-1200B, l	B2	2
HY-PF1W	Ceiling preinstall rigging frame for HX-5 & FB-120, white	B2	1
HY-WM2B	Wall/ceiling mounting bracket for HX-5, black (zero reflecti	B2	1
IP-A1PC580R E00	IP ceiling mount 8" speaker, round, 8W	B2	1
IP-A1SC15 E00	Network Horn speaker, 15 W (at PoE+), 8 W (at PoE), ONVIF	B2	1
IP-SC15MC Q D00	Network Horn speaker, up to 15 W (+/- 10%), ONVIF compatible, with onboard Microphone	B2	7
IR-520R	Infrared wall-mount receptor (receiver), reception area is a	B2	1

IR-802T CU AQD00	Infrared wireless tuner for channel A / B, Priority control, built-in FBS	B2	1
IR-820SP Y	Infrared wireless ceiling speaker, built-in receiver & 20W digital amplifier for channel A / B / 1 / 2	B2	6
IR-820SP Y 4QD00	Infrared wireless ceiling speaker, built-in receiver & 20W digital amplifier for channel A / B / 1 / 2	B2	1
IR-842PMU-AM D00	INFRARED AUDIO SYSTEM MAIN UNIT	B2	1
M-800DT-AM D00	Dante module for M-8080D-AM	B2	1
M-9000M2 CU B00	Dual channel modular mixer/matrix preamplifier, max. 8x8 modules)	B2	1
M-900MK2 UL	Modular mixer preamplifier, 8 inputs (reqs. 900 Series modules)	B2	2
M-900MK2 UL D00	Modular mixer preamplifier, 8 inputs (reqs. 900 Series modules)	B2	1
MW-41BT-AM D00	Audio Interface w/USB and Bluetooth	B2	1
N-8010MS Y A00	Standard Master station, hands free/handset, desk/surface	B2	1
N-SP80AS1 100	SIP AUDIO DOOR STATION	B2	1
N-SP80AS1 Q	SIP AUDIO DOOR STATION	B2	1
N-SP80MS1 100	SIP Multimedia Station, flexible audio & video communications, SIP & Onvif protocols	B2	8
PE-64	PENDANT SPEAKER 6W	B2	1
PJ-304	30W projection 5" speaker, white, 8 ohm/70V/100V	B2	1
Q-SS9012 D00	Speaker selector for 9000M2 Series, 12 contact inputs & 12 outputs	B2	1
RC-001T	9000M2 Series Module: Plug-in Module for control panel	B2	1
S2.4HBX	Digital Wireless 16 channel, RX2 Receiver w/ Handheld Mic	B2	1
S2.4HX	Digital Wireless 16 channel, RX1 Receiver w/ Handheld Mic.	B2	1
S4.10-RXA-AMRM3QU	Trantec S4.10 Wireless Receiver	B2	1
SC-615T	15W Paging horn, 25/70V, incl. bracket	B2	1
ST-800	Table top Mic. stand, XLR connection, compatible w/ EM-8000	B2	1
VM-3240E AMQ	Emergency 6 zone 240W extension amplifier - UL 2572 & CAN/ULC-S576	B2	1
WM-5265 H01	UHF Wireless Handheld Mic. for Speech/Vocals - 64 channels	B2	1
WM-5265-AM -M1D00	UHF Wireless Handheld Mic. for Speech/Vocals - 64 channel - Dynamic- Operates on M Band	B2	1
WM-5325 H01	UHF Wireless Beltpack Transmitter 64 channel - Operates on M Band	B2	3
WT-4820 US	Dual Wireless receiver frame, 2 whip antennas, accepts 1 or 2 WTU-4800 (1 RU)	B2	1
WT-5800-AM RM1D00	UHF Wireless Receiver- True Diversity- 64 channel - Scanning	B2	2

Terms & Conditions:

Clearance items available only to Authorized TOA Dealers (Contact TOA for a dealer near you)

- All terms & conditions of sale apply as stated from the most recent TOA Canada Price List
- Offer not valid with any other special or special terms.
- Sale in effect while quantities last.
- Quantities are limited.
- All sales are final. No returns or refunds will be accepted.
- Standard warranty applies
- All orders must be placed with a valid purchase order;

E-mail: customerservice@toacanada.com. Contact TOA's Customer Service Department for pricing to check quantities or with questions.