

TOA Canada Spring NEW Overstock Sale

Document Updated: 06/05/2026

Sale Ends May 29th, 2026

Part No.	Material Description	Discount	Qty. Avail.
Speakers			
F-1000BT	Box speaker, black, 100MM, 2-Way, 15W, 70V/8ohm	20%	55
F-1000BTWP	Box speaker, black, 100MM, 2-Way, 15W, 70V ONLY, weather resistant	20%	61
F-1000WTWP	Box speaker, white, 100MM, 2-Way, 15W, 70V ONLY, weather resistant	20%	67
F-1300WTWP	Box speaker, white, 130mm, 2-Way, 30W, 70V ONLY, weather resistant	20%	55
F-2000BTWP	Box speaker, black, 200MM, 2-Way, 60W, 70V ONLY, weather resistant	20%	2
F-2000WTWP	Box speaker, white, 200MM, 2-Way, 60W, 70V ONLY, weather resistant	20%	10
FB-3862CU-AM C00	60W, 8" speaker, Flush-mount ceiling subwoofer, low frequency, 70V, 8 ohm bypass, white	40%	80
HA-1010 Q	100V Long range outdoor array Horn speaker unit x 8	50%	5
IP-A1PC238 E00	IP ceiling mount 6" speaker, round, 8W	25%	175
PC-3CL	3W Splashproof Ceiling Speaker	25%	16
PW-1430DW	White bi-directional planewave speaker, 831 (W) x 355 (H) mm**	75%	1
SR-C8SWP	360W, 16 ohm, 2-Way Line Array, short distances, weather resistant	50%	2
TC-615M	Horn Speaker, 15W, 70V/100V White	50%	2
TH-660	Reflex horn flare, reqs. TU driver unit (incl. BR, BE & CE)	30%	2
TU-651M	50W Driver unit, reqs. TH-660 horn, Hi-Z	30%	4
YP-E5000	Universal assist ear speakers for WT-5100, 3.5mm connector	50%	16
Modules			
B-21S D00	900 Series Module: Bridging module w/remote control volume	25%	31
BT-01 QV	900 Series Bluetooth Module	25%	83
D-2000CB	CobraNet interface module, CobraNet: 100BASE-TX, RJ45 connector for D-2008SP Digital Mixing Processor Unit	50%	2
D-2000DA1	Line output module, 4 channels, XLR for D-2008SP Digital Mixing Processor Unit	50%	7
E-03R D00	900 Series Module: Processor module for F-122C speakers	25%	56
E-07S	900 Series Module: Low-frequency line output for HB-1/FB-100 low frequency drivers	25%	4
L-01F	900 Series Module: Line in module, XLR-F, 600 ohm	25%	29

M-01P		900 Series Module: Mic. module c/w gain, phantom, phone plug, 600 ohm	25%	10
M-03P		900 Series Module: Mic. module c/w gain, phone plug, 50K ohm	25%	21
M-51F	D00	900 Series Module: Mic. module, gate, gain, phantom, XLR-F, 600 ohm	25%	16
M-61S	T D00	900 Series Module: Mic module, compressor gain, phantom, terminal block, 600 ohm	25%	46
S-01S	T D00	900 Series Module: 1KHz sine wave signal module, terminal block	25%	35
T-12S		900 Series Mod: Aux input + line o/p controls, music-on-hold, screws w/passive mute circuit, 220K ohm	30%	2
U-01P		900 Series Module: Aux. module, c/w gain control, phone plug, 220K ohm	30%	6
U-12S	T	900 Series Module: Aux. module, c/w variable mute-depth, gain control, terminal block, 220K ohm	30%	9
U-13S	D00	900 Series Module: Aux. module, w/ EQ, mute-receive, Mono, screws, 220K ohm	25%	28
U-14R	D00	900 Series Module: Dual input priority module c/w AGC	30%	6
U-43R		900 Series Module: Aux. module, w/EQ, mute-send, 220K ohm	30%	2
U-43R	D00	900 Series Module: Aux. module, w/EQ, mute-send, 220K ohm	30%	6
U-43S		900 Series Module: Aux. module, w/EQ, mute-send, 220K ohm	30%	3
U-61S	T D00	900 Series Module: Aux. module, gain control, compressor, terminal block, 220K ohm	25%	29
V-01S	D00	900 Series Module: Remote master volume control (VCA) module	25%	36

Amplifiers/Mixers/Audio Processors

A-2060	CU	60W mixer/amplifier (5 channel input, Mic./Line/PBX), phantom power, auto-mute	50%	4
A-2120	CU	120W mixer/amplifier (5 channel input, Mic./Line/PBX), phantom power, auto-mute	25%	8
A-2240	CU	240W mixer/amplifier (5 channel input, Mic./Line/PBX), phantom power, auto-mute	25%	8
A-5006	3CUD00	60W, 4 input Mixer/Amplifier, DSP, 4ohm, 70V	50%	10
A-903MK2	UL D00	30W mixer power amplifier (8 channel input slots, (reqs. 900 series modules), permits paging priority	50%	13
A-906MK2	UL D00	60W mixer power amplifier (8 channel input slots, reqs. 900 series modules), permits paging priority	25%	10
CA-130	F01	30W Mobile amplifier 12 Volt DC, Mic.	50%	4
D-901	US	Digital modular mixer, max. 12x8	50%	3
DP-L2	CU	Digital ambient noise controller	30%	4
M-9000M2	CU B00	Dual channel modular mixer/matrix preamplifier, max. 8x8 - (uses A-9000 & 900 Series Modules)	30%	210

MP-032B A00	Monitor panel for aural & visual monitoring for multi-channel, Analog, incl. rack mounting	50%	21
MP-1216 US	16 channel audio monitor panel, LED, linkable to 32 channels	50%	1
P-9060DH CU B00	60W dual channel power amplifier, bal. line level input, 70V	25%	12
P-9120DH CU B00	120W dual channel power amplifier, bal. line level input, 70V	50%	2
SO-MIX-T	Remote mixer XLR/RCA input, balanced output (24V 600mA power supply req.)	10%	13
VP-2064	SX power amplifier, 4 channels, 60 watts (<i>VP-200VX required for each channel</i>) (<i>VX-2000DS required</i>)	60%	6

Intercoms

NF-2 D00	Lightweight Window Intercom System	50%	2
RS-190	N-8000 4-wire Full-Duplex Sub Station	50%	58
RS-480VSET-AM	N-8000 Video Intercom Station & Intercom Station w/ Colour Camera	50%	7

Brackets & Accessories

ACC-SPLIT-2W	Passive antenna splitter for TOA 5000 Series Wireless Microphone	50%	1
BB-580 QV	Back box for PC-580R & PC-580RV speakers	10%	3
BC-5000-12	Battery charger, simultaneously charge 12 Mics. (AD-5000-6 req.) for 5000 Series UHF Wireless	25%	7
BP-900A -CEB02	Battery for use with the TS-820/920 Series Conference Systems, rechargeable	25%	8
BP-920 Y B00	Battery for TS-820/920 chairman/delegate units	25%	2
BX-9F	Flush back-box for wall amps W-906/912A	25%	12
BX-9S	Surface back-box for wall amps W-906/912A	30%	16
HY-BC2W QV	Enclosure for FB-3862CU subwoofer, white	30%	63
HY-BH10B	Board hanger bracket, F-1000, F1300, black	60%	20
HY-CL10B	Cluster bracket for F-1000/F-1300 Speakers, black	60%	25
HY-CL20B	Cluster bracket for F-2000 Speakers, black	60%	22
HY-CM10B	Ceiling mount bracket for F-1000/F-1300 Speakers, black	60%	10
HY-CM10W	Ceiling mount bracket for F-1000/F-1300 Speakers, white	60%	13
HY-CM20B	Ceiling mount bracketfor F-2000 Speakers, black	60%	17
HY-CM20W	Ceiling mount bracketfor F-2000 Speakers, white	60%	12
IR-800D QV	Infrared wireless distributor for IR-800	40%	294
IR-801AF US DQD00	Audio Interface Unit, Infrared & Audio signal combiner & splitter, w/ Mic. priority control for IR-800 Series	20%	67

IR-802T CU 1QD00	Infrared wireless tuner for channel 1 / 2, Built-in FBS, Priority control for separate mode for IR-800 Series	20%	144
IR-842BAG-AM D00	Rugged carrying bag for IR-842P	30%	421
M-800FPB QV	Remote Control Panel Plate for M-800/M-802RC, Black	10%	99
M-800FPW QV	Remote Control Panel Plate for M-800/M-802RC, White	10%	96
M-800RCB-AM D00	Remote Volume Control Panel for the M-8080D Series, Black	10%	129
M-802RC-AM D00	Remote Volume Control Panel w/ Audio Out for the M-8080D Series, White	10%	66
M-802RCB-AM D00	Remote Volume Control Panel w/ Audio Out for the M-8080D Series, Black	10%	60
M-822IOB-AM D00	Remote Audio I/O Panel for the M-8080D Series, Black	10%	46
MB-480V4-AM	Rack mounting panel for up to 4x IF-480V	75%	4
MB-TS900	Rack mount kit for TS-800/900 central units	50%	33
PF-013B	19" Perforated Rack Panel, 1RU	50%	10
Q-BB-580PW QV	Square surface mount back box for PC-580S, off-white	25%	42
SO-MIX-PLATE QV	2-Gang accessory wall plate for SO-MIX-T-24V.	25%	47
SP-1100	Wall mounting bracket for megaphone ER-1203, ER-1206	20%	38
SR-FS4	Slim type, floor stand for SR-S4L	50%	11
SR-PB1W-AM	Panning wall mount bracket for the SR-M Series, white	75%	4
SR-RF8WP	Rigging Frame, weather resistant, SR-C8L, SR-C8S, or SR-C15B	50%	4
SR-SB8	Rigging support bracket in conjunction w/ the optional SR-RF8	50%	4
SR-TP12	Mid type - tilt joint plate for the Line Array Type A Series	50%	7
SX-2000AO A01	SX audio output interface, not supervised (<i>VX-2000DS required</i>)	50%	1
SX-2000SM A01	SX system main processor (<i>VX-2000DS required</i>)	50%	1
SX-200IP	Data bridge between the N-8000 and SX-2000	50%	6
WB-AM1BWC AM	Mounting bracket for AM-1 Microphone system	50%	3
YR-770-10M	Extension cord for the TS 700 Conference Series, 10 meters	65%	14
YR-770-2M	Extension cord for the TS 700 Conference Series, 2 meters	65%	15
ZM-9003	9000M2 Series Amp: Remote switch panel, 6 switches	50%	14
Microphones & Megaphones			
AM-1CQAM	Control Unit for AM-1 Real-time steering array microphone (AD-246 required)	25%	5
ER-1206	6W, splash-proof hand grip type megaphone, clear	20%	4

ER-1206S		6W, splash-proof hand grip type megaphone w/ siren, red	20%	3
ER-2215W		15W, shoulder type megaphone w/ whistle	30%	2
ER-2230W	F00	30W, shoulder type megaphone w/ whistle	20%	2
ER-2930W		30W, shoulder type megaphone w/ whistle, wireless	40%	1
ER-2930W	F00	30W, shoulder type megaphone w/ whistle, wireless	40%	4
ER-3215	F00	15W, hand grip type megaphone (incl. shoulder strap)	20%	10
ER-520		6W, compact hand grip type megaphone	20%	31
ER-520W		6W, compact hand grip type megaphone w/ whistle	20%	33
ER-604W		10W, Mega talk/portable PA System, incl. shoulder strap	40%	2
IR-310M	Y PQD00	Hand Free infrared wireless Mic. (channel A / 1) for IR-800 Series	20%	155
MIC-SJ22-B-R		Headset Mic., black, 3.5mm connector	50%	4
MIC-SJ22-P-R		Headset Mic., beige, 3.5mm connector	50%	2
MIC-SJ66-BL		Aerobic headset Mic., blue gooseneck. 3.5mm connector	50%	1
MIC-SJ66-YE		Aerobic headset Mic., yellow gooseneck. 3.5mm connector	50%	2
MIC-SJEM77-P		Ear worn Mic., beige, 3.5mm connector	50%	8
MIC-X212-P-R		Pro lavalier, beige, mini XLR (TA4F) connector	50%	2
MIC-X22-B-R		Headset Mic., black, mini XLR (TA4F) connector	50%	1
MIC-X22-P-R		Headset Mic., beige, mini XLR (TA4F) connector	50%	4
MIC-X33		Headset Mic., black, mini XLR (TA4F) connector	50%	4
MIC-X55		Lavalier Mic., black, mini XLR (TA4F) connector	50%	4
MIC-X66-BK		Aerobic headset Mic., black gooseneck, mini XLR (TA4F) connector	50%	3
MIC-X66-YE		Aerobic headset Mic., yellow gooseneck, mini XLR (TA4F) connector	50%	3
MIC-XEM77-P		Ear worn Mic., beige, mini XLR (TA4F) connector	50%	3
S2.4-ANT	QV	S2.4 Series Microphone Antenna	50%	28
S2.4BBX	QV	S2.4 Series Digital Wireless 16 channel, RX2 Receiver w/ 2 x BTX Beltpacks	50%	25
S2.4-BTX-G3		S2.4 Series Digital Wireless belt pack transmitter w/ LCD & Lapel Mic. - S2.4-LMO	50%	37
S2.4BX		S2.4 Series Digital Wireless 16 channel, RX1 Receiver w/ BTX Beltpack	50%	41
S2.4HBX		S2.4 Series Digital Wireless 16 channel, RX2 Receiver w/ Handheld Mic. & BTX Beltpack	50%	8
S2.4-HDX-G3		S2.4 Series Digital Wireless Handheld Mic. w/ LCD	50%	3
S2.4-HMO	QV	Headworn Mic. Omnidirectional for S2.4 Series	50%	45
S2.4-HMU	QV	Headworn Mic. Unidirectional for S2.4 Series	50%	5
S2.4-LMO	QV	Lavalier Mic. Omnidirectional for S2.4 Series	50%	19

S2.4-RX1-G3	1 channel Receiver w/ LCD (Half size), 16 available channels for S2.4 Series	50%	1
S2.4-RX2-G3	2 channel Receiver w/ LCD (1 Unit size), 16 available channels for S2.4 Series	50%	19
S4.10-HDX-AMWM3QU	Trantec S4.10 dynamic. handheld Mic.	50%	30
S4.10-L-AM RM3QU	Trantec S4.10 wireless system w/ belt pack transmitter w/ lavalier, up to 16 channels	50%	25
S4.10-LTX-AMWM3QU	Trantec S4.10 belt pack transmitter w/ lavalier	50%	58
S4.10-RXA-AMRM3QU	Trantec S4.10 wireless receiver, up to 16 channels	50%	19
S5.3-HC-H2USQ	Handheld condenser wireless microphone and true diversity tuner kit, 12 channels for S5.3 Series	25%	2
S5.3-HCX-H2 Q	Handheld cardioid condenser wireless microphone for S5.3 Series	50%	1
S5.3-HDX-H2 Q	Handheld cardioid dynamic wireless microphone for S5.3 Series	40%	8
S5.3-RX-H2 Q	UHF Wireless tuner, true diversity, 12 channels for S5.3 Series	50%	7
YP-M301	WM-2100 Headset Microphone, 3.5 mm monaural mini plug	50%	7

TOA Canada Spring B-Stock Sale

Document Updated: 06/05/2026

Sale Ends May 29th, 2026

Part No.	Material Description	Discount	Qty. Avail.
Condition B1 - Factory sealed discontinued items or factory seal broken but			
A-2240 CU	240W mixer/amplifier (5 channel input, Mic./Line/PBX), phantom power, auto-mute	50%	1
AT-100 AM QV	10k ohm volume control	50%	1
AT-10K AM QV	100W Decora-Style 10k ohm single point volume control	50%	1
BG-2035 CU D00	35W, 5-Input mixer/amplifier, module slot, 4 ohm/25V/70V, MOH/Zone 2	50%	1
BS-678	6W, 2 x 2.5" speakers, Wall mount , wood cabinet, 70V (sold in pairs)	50%	2
BS-680FC	6W, 6" double cone speaker, Wall mount , metal body, 70V	50%	1
BS-680U	6W, 6" double cone type spkr., surface mount, metal case UL/ULC, 25V/70V	50%	2
CS-304	6W, 2 x 2.5" speakers, surface mount, metal case UL/ULC, 25V/70V	50%	1
EQ-0101A Q	Equalizer for HA-1010** (special order)	50%	2
EV-350R L	Digital Record/Playback Announcer, mountable memory cards, Headphone output, Mic input	50%	4
H-2 EX	12W, 2-way, dome-shaped 4" speaker, + 1" tweeter, wall/ceiling-mount, 4 ohm/70V	50%	1
HY-1200HW	Mounting bracket, for horizontal speaker mounting, for HS-1200 speakers, white	50%	2
HY-1200VB	Mounting bracket, for vertical speaker mounting, for HS-1200 speakers, black	50%	3
HY-1200VW	Mounting bracket, for vertical speaker mounting, for HS-1200 speakers, white	50%	1
HY-C0801W	Ceiling Mount Bracket for HS series speakers, HS-1200WT, HS-1500WT	50%	1
HY-W0801W	Wall mount bracket for, HS-1200BT, HS-1500BT, white	50%	2
IP-A1SC15 E00	Network Horn speaker, 15 W (at PoE+), 8 W (at PoE), ONVIF compatible	50%	1
IP-SC15MC Q D00	Network Horn speaker, up to 15 W (+/- 10%), ONVIF compatible, with onboard Microphone	50%	1
IR-310BC US	Battery charger for the IR-310M	50%	1
IR-801AF US	Single channel (A), wireless tuner w/ output to control Infrared Mic.	50%	1
IT-450	Input transformer	50%	1
M-21S D00	900 Series Module: Mic. module, remote volume, gain, phantom, screws, 600 ohm	50%	1
M-41S D00	900 Series Module: Mic. module, mute-send, screws, 600 ohm	50%	1
M-900MK2 UL D00	Modular mixer preamplifier, 8 inputs (reqs. 900 Series modules)	50%	1
MT-200 F00	MATCHING TRANSFORMER	50%	2

MW-41BT-AM D00	Audio Interface w/ USB & Bluetooth (power supply incl.)	50%	1
N-SP80MS1 C00	IP Audio Window Intercom Kit, 2-way (power supply incl.), Weather Resistant	50%	1
PE-604BU	60W Pendant 5" speaker, UL1480 UUMW, ULC-S541, 8 ohm/70V/100V, black	50%	1
S2.4-RX2-G3	2 channel Receiver w/ LCD (1 Unit size), 16 available channels	50%	1
SC-615	15W Paging horn, 8 ohm, incl. bracket	50%	1
SP-11NAM D00	900 Series SIP module complete w/ AD-1215P (Asterisk & CUCM compliant)	50%	1
SP-201	Speaker horn bracket for wall mount, and on w/ YS-60B	50%	1
SR-WB3	Wall mounting bracket, SR-H3S, SR-H3L, SR-H2S, SR-H2L	50%	1
SR-WB4	Slim type, wall mount bracket, SR-S4L	50%	5
TS-822 Y E00	TS-820 system: Delegate Unit	50%	3
TT-104B 304L	Program timer w/ 4 outputs & controls 4 different broadcasts	50%	1
UC-4SC615 Q E01	Network Horn Speaker with Microphone	50%	1
WH-4000A	Aerobic Headset Mic., (speech), condenser, unidirectional, 3.5mm connector	50%	2
WM-2100 01	Portable Receiver, 5 channels	50%	2
WM-5265 H01	UHF Wireless Handheld Mic. for Speech/Vocals - 64 channel - Dynamic- Operates on H Band	50%	1
ZM-9012 B00	9000M2/M-864D Remote Control Panel - 9000M2 use reqs. RC-001T & AD-246	50%	2

Condition B2 - Packaging disturbed or cosmetic damage to product and/or refurbished.

A-812D 3CUE00	120W digital mixer/amplifier (8 channel input, Mic./Line/ two optional module slot), incl. 1 Mic./Emergency, DSP, EQ	70%	1
A-906MK2 UL D00	60W mixer power amplifier (8 channel input slots, reqs. 900 series modules), permits paging priority	70%	2
BA-260 CU	60W, 1 input mixer/amplifier, one line input, 4 ohm/25V/70V, terminal block or RCA jack	70%	1
BS-1034	10W, Slim box speaker, white, 70V	70%	2
BS-1034S	10W, Slim box speaker, silver, 70V	70%	1
C-001T B00	9000M2 Series Module: I/O control module, 8 inputs 8 outputs	70%	1
D-001T	9000M2 Series Module: Dual Mic./line input w/ DSP module & balanced	70%	1
DA-250DH CU A00	Digital multi-channel amplifier (250W X 2 channels, 70V)	70%	1
EV-20R US D00	Digital sound repeater, 3W amp, USB interface, line O/P, rack mountable (AD-246 req.)	70%	1
F-2352C	30W, co-axial 5", ceiling speaker + dome tweeter, 8 ohm or 25/70V selectable taps, c/w Reinforcement Ring & metal back can	70%	1
H-3 EX	30W, wide dispersion, 2 x 4" speaker, + 1" tweeter, wall mount, 8/16 ohm/70V	70%	3

HX-7W-WP F00	SPEAKER SYSTEM	70%	1
HY-C0801	Ceiling Mount Bracket for HS series speakers, HS-1200B, HS-1500B	70%	2
HY-PF1W	Ceiling preinstall rigging frame for HX-5 & FB-120, white	70%	1
HY-WM2B	Wall/ceiling mounting bracket for HX-5, black (zero reflection)	70%	1
IP-A1PC580R E00	IP ceiling mount 8" speaker, round, 8W	70%	1
IP-A1SC15 E00	Network Horn speaker, 15 W (at PoE+), 8 W (at PoE), ONVIF compatible	70%	1
IP-SC15MC Q D00	Network Horn speaker, up to 15 W (+/- 10%), ONVIF compatible, with onboard Microphone	70%	7
IR-520R	Infrared wall-mount receptor (receiver), reception area is approx. 15m line of sight	70%	1
IR-802T CU A QD00	Infrared wireless tuner for channel A / B, Priority control, built-in FBS	70%	1
IR-820SP Y	Infrared wireless ceiling speaker, built-in receiver & 20W digital amplifier	70%	6
IR-820SP Y 4QD00	Infrared wireless ceiling speaker, built-in receiver & 20W digital amplifier for channel A / B / 1 / 2	70%	1
M-800DT-AM D00	Dante module for M-8080D-AM	70%	1
M-9000M2 CU B00	Dual channel modular mixer/matrix preamplifier, max. 8x8 - (uses A-9000 & 900 Series Modules)	70%	1
M-900MK2 UL	Modular mixer preamplifier, 8 inputs (reqs. 900 Series modules)	70%	2
M-900MK2 UL D00	Modular mixer preamplifier, 8 inputs (reqs. 900 Series modules)	70%	1
MB-WT4	Rack mount for dual WT-5800, WT-5805, WT-4820, IR tuner, EV-20R, (1 RU)	70%	1
MW-41BT-AM D00	Audio Interface w/USB and Bluetooth	70%	1
N-8010MS Y A00	Standard Master station, hands free/handset, desk/surface mount	70%	1
N-SP80AS1 100	SIP AUDIO DOOR STATION	70%	1
N-SP80MS1 100	SIP Multimedia Station, flexible audio & video communications, SIP & Onvif protocols	70%	8
PE-64	PENDANT SPEAKER 6W	70%	1
PJ-304	30W projection 5" speaker, white, 8 ohm/70V/100V	70%	1
Q-SS9012 D00	Speaker selector for 9000M2 Series, 12 contact inputs & 12 speaker outputs (AD-246 req.)	70%	1
RC-001T	9000M2 Series Module: Plug-in Module for control panel	70%	1
S2.4HBX	Digital Wireless 16 channel, RX2 Receiver w/ Handheld Mic. & BTX Beltpack	70%	1
S2.4HX	Digital Wireless 16 channel, RX1 Receiver w/ Handheld Mic.	70%	1
SC-615T	15W Paging horn, 25/70V, incl. bracket	70%	1
ST-800	Table top Mic. stand, XLR connection, compatible w/ EM-800	70%	1
VM-3240E AMQ	Emergency 6 zone 240W extension amplifier - UL 2572 & CAN/ULC-S576	70%	1

WM-5265 H01	UHF Wireless Handheld Mic. for Speech/Vocals - 64 channel - Dynamic- Operates on H Band	70%	1
WM-5265-AM -M1D00	UHF Wireless Handheld Mic. for Speech/Vocals - 64 channel - Dynamic- Operates on M Band	70%	1
WM-5325 H01	UHF Wireless Beltpack Transmitter 64 channel - Operates on H Band (Mic. selection req.)	70%	4
WT-4820 US	Dual Wireless receiver frame, 2 whip antennas, accepts 1 or 2 WTU-4800 (1 RU)	70%	1
WT-5800-AM RM1D00	UHF Wireless Receiver- True Diversity- 64 channel - Scanner, 2 Whip Antennas, (1U), Operates on M Band	70%	2

Terms & Conditions:

Clearance items available only to Authorized TOA Dealers (Contact TOA for a dealer near you)

- All terms & conditions of sale apply as stated in TOA's newest Price List.
- Offer not valid with any other special or special terms.
- Sale in effect while quantities last.
- Quantities are limited.
- All sales are final. No returns or refunds will be accepted.
- Standard warranty applies
- All orders must be placed with a valid purchase order;

E-mail: customerservice@toacanada.com. Contact TOA's Customer Service Department for pricing to check quantities or with questions.